



LED Site Light Area Flood Light | Optional Photocell | 20W to 320W

Wattage	30w, 50w, 100w, 135w, 180w, 240w, 320w
Lumens	30W: 4200lm, 50w: 7000lm, 100w: 14,000lm, 135w: 18,900lm, 180w: 25,200lm, 240w: 33600lm, 320w: 44,800lm
Lumens per watt	140lm/w
CCT	4000k
IP Rating	IP65
IK Rating	IK07
Input Voltage:	110V
Beam Angle:	110°
Dimensions	30w: 257mm x 247mm x 50mm 50w: 257mm x 247mm x 50mm 100w: 325mm x 236mm x 48mm 135w: 345mm x 285mm x 55mm 180w: 395mm x 320mm x 78mm 240w: 480mm x 374mm x 78mm 320w: 555mm x 425mm x 78mm





LED Site Light Area Flood Light | Optional Photocell | 20W to 320W

CRI	>80
Working Temperature:	-30°C to +45°C
Materials	Body/Housing: Die-cast Aluminum Lens: Glass
Application	Ideal for Construction sites (day or night work), Roadworks and highway maintenance, Emergency services and disaster response, Outdoor events and festivals, Railway and infrastructure maintenance, Warehouses and temporary storage areas, Security lighting for large outdoor areas, Utility and power maintenance tasks, Military or defense field operations.
Lifespan:	>50,000 hours
Certificates	UKCA, CE
Warranty	3-year warranty

