



Site Light Floodlight - 50W | 100W | 150W | 200W

Wattage	50W, 100W, 150W, 200W
Lumens	100lm/w
Lumens per watt	5000lm, 10,000lm, 15,000lm, 20,000lm
CCT	4000k
IP Rating	IP65
IK Rating	IK07
Input Voltage:	110V
Beam Angle:	110°
Lifespan:	.>50,000 hours
Dimensions	50w: 216mm x 212mm x 32mm 100w: 251mm x 290mm x 37mm 150w: 311mm x 348mm x 40mm 200w: 374mm x 414mm x 41mm





Site Light Floodlight - 50W | 100W | 150W | 200W

CRI	>80
-----	-----

Working Temperature:	-20°C to +45°C
----------------------	----------------

Materials	Body/Housing: Die-cast Aluminum Lens: Glass
-----------	--

Application	Ideal for Construction sites (day or night work), Roadworks and highway maintenance, Emergency services and disaster response, Outdoor events and festivals, Railway and infrastructure maintenance, Warehouses and temporary storage areas, Security lighting for large outdoor areas, Utility and power maintenance tasks, Military or defense field operations.
-------------	--

Certificates	UKCA, CE
--------------	----------

Warranty	3-year warranty
----------	-----------------

