



ATEX Lighting

LED Hazardous Explosion Proof Flood light

Wattage	40w (zone 2), 80w, 100w, 150w, 200w, 300w, 400w
---------	---

Lumens	11200lm, 14000lm, 21000lm, 28000lm, 42000lm, 56000lm
--------	--

Lumens per watt	140lm/W
-----------------	---------

CCT	5000k
-----	-------

IP Rating	IP66
-----------	------

IK Rating	IKo8 (glass cover) IK10 (with wire guard)
-----------	--

Input Voltage:	200-250VAC
----------------	------------

Beam Angle:	90°
-------------	-----

Lifespan:	150,000 operation hours at 55°c
-----------	---------------------------------

Warranty	5-year warranty
----------	-----------------





ATEX Lighting

LED Hazardous Explosion Proof Flood light

ATEX	II 2 G Ex eb mb IICT6... T ₄ Gb
Certification	II 2 D Ex te IICT80°C... T100°C Db

IECEX	Ex eb mb IICT6... T ₄ Gb
Certification	Ex te IICT80°C... T100°C Db

Zone:	Zones 1,2, 21,22
-------	------------------

Salt	1000 hours
Spray:	

Operation	40w, 80w, 100w, 150w, 200w:
Temperature	T ₅ : -40°C to +45°C
	T ₆ : -40°C to +40°C
	300w:
	T ₅ : only -40°C to +40°C
	400w:
	T ₅ : -40°C to +25°C






ATEX Lighting

LED Hazardous Explosion Proof Flood light

Photometric

40 Degree




AVERAGE BEAM ANGLE(50%):38.6 DEG

UNIT:cd

— C0/180,38.7°
— C90/270,38.5°

60 Degree




AVERAGE BEAM ANGLE(50%):52.5 DEG

UNIT:cd

— V 0.0DEG PLAN,52.3
— H 0.0DEG PLAN,52.7

90 Degree



AVERAGE BEAM ANGLE(50%):82.8 DEG

UNIT:cd

— V 0.0DEG PLAN,83.2
— H 0.0DEG PLAN,82.4





ATEX Lighting

LED Hazardous Explosion Proof Flood light

Cable Entries

Compatible with NPT1 thread with an adapter

Top: 3/4 NPT (standard),
M25

Wire outlet

Side: 3/4 NPT (standard),
M20, M25, 1/2NPT

Wire outlet

Side: 3/4 NPT (standard),
M20, M25, 1/2NPT

