

ATEX Lighting



Atex LED Hazardous Explosion Proof High Bay – Zone 1 – 120W/150W/200W/250W/400W

Technical Data

Chips Type/Brand: SOSEN Driver

Wattage: 120W
150W
200W
250W
400W

Lumens: 140Lm/W

Colour Temperature: 5000K

Dimmable No

Beam Angle: 120°

Voltage input: AC100-277V

IP Rating: IP66

Lifespan: 50,000 Hours

CRI: >70

IK Rating: IK10

Working Temperature: -40C-+50C

Power Factor: >0.9



ATEX Lighting



Atex LED Hazardous Explosion Proof High Bay – Zone 1 – 120W/150W/200W/250W/400W

Atex Certification

II2 G Ex mb eb IICT4 Gb
II2 D Ex tb IIICT135°C Db IP66
II3 G Ex ec IICT3 Gc
II2 D Ex tb IIICT85°C Db IP66

IECEX Certification

Ex mb eb IICT4 Gb
Ex tb IIICT135°C Db IP66
Ex ec IICT3 Gc
Ex tb IIICT85°C Db IP66

Warranty:

5 Years

Dimensions(CM):

37.1 x 37.0 x 19.7

Certificates:

WTL, UL 1598, UL 844, ECEX, ATEX, ABS CB, CSA, CE, RoHS

Material:

Aluminium, PC and Tempered/Toughened Glass

Application:

Ceiling Mounting, Wall Mounting, Pole Pendent Mounting, Stanchion Mounting. Any Atex rated area inc Refineries and fuel depots, marine vessels, chemical production and processing, food processing, mining, wineries, other high humidity, and dusty places.






RoHS
COMPLIANT




LED
SUPPLY & FIT